SONANCE

ARCHITECTURAL SERIES DATA SHEET

AS38RS

TECHNICAL SPECIFICATIONS

SKU
AS38RS
93401
UOM
Each

Tweeter 0.75" (19mm) ceramic dome, Ferrofluid-cooled, in acoustic back chamber

Woofer 3.5" (89mm) carbon fiber/Rohacell laminated cone with a rubber surround

Frequency Response 75Hz - 20Hz +/-3dB

Impedence 10 Ohms nominal, 8 Ohms minimum

Sensitivity 83dB SPL (2.83v/1 meter)

Power Handling 100 Watts maximum

High Pass Filter 125Hz 6dB per Octave

Dimensions (DiaxD) 3.875" x 3.5" (99mm x 89mm)

Grille Round 4" (102mm) & Square 4" (102mm x 102mm) perforated steel grilles

Shipping Weight 3.5 lbs (1.58kg)

RECOMMENDED PRODUCTS

1/2" Gypsum MP AS Discreet Round / Each	93045
1/2" Gypsum MP AS Discreet Square / Each	93046
5/8" Gypsum MP AS Discreet Round / Each	93047
5/8" Gypsum MP AS Discreet Square / Each	93048
Small Retrofit Enclosure / Pair	92443
5/8" SS MP AS Discreet RS / Each	93053
SS Router Template AS Discreet RS / Pair	93057

ASSOCIATED PRODUCTS

Sonamp 2-100 / Each	93091
Sonamp 12-50 / Each	93092
Sonamp DSP 2-150 MKII / Each	93378
Sonamp DSP 8-130 MKII / Each	93331

DIMENSIONAL DRAWINGS



3.875" (99mm) **Front View**

. ت

(89mm)

Side View

LIMITED FIVE (5) YEAR WARRANTY Sonance warrants to the first end-user purchaser that this Sonance-brand product ("Product"), when purchased from an authorized Sonance Dealer/Distributor, will be free from defective workmanship and materials for the period stated above. Sonance will at its option and expense during the warranty period, either repair the defect or replace the Product with a new or remanufactured Product or a reasonable equivalent. For more details please refer to the product manual.

©2021 Sonance. All rights reserved. Sonance is a registered trademarks of Dana Innovations. Due to continuous product improvement, all features and specifications are subject to change without notice. For the latest Sonance product specification information visit our website at www.sonance.com.