SONANCE

VISUAL EXPERIENCE DATA SHEET

VX62 | VX66

TECHNICAL SPECIFICATIONS

VX62 SKU 96003 - Pair

Tweeter 1" (25mm) cloth dome. Ferrofluidcooled, acoustic back chamber

3.84" (97.6mm)

9 lbs. (4.1kg)

Woofer 6.5" (165mm) textured polypropylene

cone, rubber surround

Dispersion Technology Sinusoidal textured waveguide

Frequency Response 45Hz - 20kHz +/-3dB

Impedance 8 ohms nominal; 6 ohms minimum

Power Handling (RMS) 5 watts minimum: 125 watts maximum

Sensitivity (2.83V/1m)

Mounting Technology Flex Frame 1 or 2-stage, 4 x RotoLock® Clamps

Micro Trim Grille (WxH) 8.23" x 12.12" (208.9mm x 307.7mm)

Trimless Grille (WxH) 7.88" x 11.77" (200.1mm x 298.9mm)

Speaker Mounting Depth (D) 3.48" (88.3mm)

Mounting Depth + Retrofit Encl.

Cut-Out Dims (WxH)

Shipping Weight

96004 - Pair

VX66

1" (25mm) ceramic dome. Ferrofluidcooled, acoustic back chamber

6.5" (165mm) Kevlar/Nomex cone,

rubber surround

Sinusoidal textured waveguide

43Hz - 20kHz +/-3dB

8 ohms nominal; 6 ohms minimum

5 watts minimum; 140 watts maximum

90dB SPL

Flex Frame 1 or 2-stage, 4 x RotoLock® Clamps

8.23" x 12.12" (208.9mm x 307.7mm)

7.88" x 11.77" (200.1mm x 298.9mm)


3.48" (88.3mm)

3.84" (97.6mm)

6.9375" x 10.75" (176mm x 273mm)

10 lbs. (4.5kg)

DIMENSIONAL DRAWINGS




Cut-Out Width **Front View**



Mounting Depth (Open Back)

Side View



6.9375" x 10.75" (176mm x 273mm)

Mounting Depth + Retrofit Enclosure

Side View

VX 6" RECTANGLE **ACCESSORIES**

VX6-GRILLE-T

6" Micro Trim Rectangle Grille / Pair 93581

VX6-GRILLE-NT

6" Trimless Rectangle Grille / Pair 93582

VX6-ENCL

6" Rectangle Enclosure / Pair 96342

FLEXBRK-6

6" Rectangle Flex Bracket / 5x Pair 92336

LIMITED LIFETIME WARRANTY

Sonance warrants to the first end-user purchaser that this Sonance-brand product ("Product"), when purchased from an authorized Sonance Dealer/Distributor, will be free from defective workmanship and materials for the life of the Product, except for the grille, which is warranted for five (5) years. Sonance will at its option and expense either repair the defect or replace the Product with a new or remanufactured Product or a reasonable equivalent. ©2024 Sonance. All rights reserved. Sonance is a registered trademarks of Dana Innovations. Due to continuous product improvement, all features and specifications are subject to change without notice. For the latest Sonance product specification information visit our website at www.sonance.com. 991 Calle Amanecer • San Clemente, CA 92673 USA • Phone: (949) 492-7777 • Fax: (949) 361-5151 • Technical Support: (949) 492-7777 01.16.2024